







GRAVITY VALVES FOR PET STRETCH BLOW MOULDING MACHINES

Model No.	Size	Symbol	Description
PV-1/2-3-12H*	G 1/2		G 1/2" BSP 3/2 High Pressure blow solenoid valve Main line Pressure : 3 to 20 bar Pilot line Pressure : 5 to 9 bar Flow at 5 bar : 3600 NLPM
PV-1/2-3-12D*	G 1/2		G 1/2" BSP 3/2 Dual Pressure blow solenoid valve Main line Pressure : 3 to 20 bar Pilot line Pressure : 5 to 9 bar Flow at 5 bar : 3600 NLPM
PV-3/4-2-12C*	G 3/4		2/2 Normally open Cushion solenoid valve Main line Pressure : 2.5 to 10 bar Pilot line Pressure : 5 to 9 bar
PV-1-2-12C *	G 1		
RH-1/2	G 1/2		G 1/2" BSP High pressure regulator Inlet Pressure : 5 to 30 bar Regulated Pressure : 0 to 25 bar Orifice : 12 mm Flow at 5 bar : 2500 NLPM
RHD-1/2			Diaphragm Type G 1/2" BSP High pressure regulator Inlet Pressure : 5 to 40 bar Regulated Pressure : 0 to 25 bar
VR-1/4 *	G 1/4		G 1/4" BSP Valve regulator assembly
VR-1/2 *	G 1/2		G 1/2" BSP Valve regulator assembly
SV-1/4-3-12NCEP*	G 1/4		3/2 Solenoid-Air Spring (N.C) with external pilot
SV-1/2-3-12NCEP*	G 1/2		
SV-1/4-5-12P*	G 1/4		3/2 Solenoid-Air Spring for Press (VR-1/4 & VR-1/2)
SV-1/2-5-12P*	G 1/2		

* Add voltage suffix as above to model no. : 'A' for 230 VAC and 'D' for 24 VDC.